

Type D Pressure Gauge



- Even with reciprocating pumps, gauge provides quick, accurate response to pressure changes and minimizes fluctuations with a built-in dampening mechanism
- Temperature range: -50°F to 180°F
Liquid surrounding gauge mechanism minimizes wear from vibration and mechanical shock
- Heavy duty seals create watertight barrier around gauge mechanism
- Impact resistant, clear polymer lens
- Connects with threaded female 2" line pipe

To order, specify:

- ① Unit of measure and pressure range
- ② Type of service
- ③ RETSCO part number

Pressure Range	Standard Service	Salt Water Service	Corrosive Fluid Service
1,000 psi	771111	771121	771131
3,000 psi	771211	771221	771231
5,000 psi	771311	771321	771331
6,000 psi	771411	771411	771431
7,000 kPa	772111	772121	772131
21,000 kPa	772211	772221	772231
35,000 kPa	772311	772321	772331
42,000 kPa	772411	772421	772431
70 Bar	773111	773121	773131
210 Bar	773211	773221	773231
350 Bar	773311	773321	773331
420 Bar	773411	773421	773431

Also available in kg/cm²

Shipping Weights:	Standard service	26 lbs (11.9 kg)
	Salt water service	35 lbs (16 kg)
	Corrosive service	26 lbs (11.9 kg)

GAUGE REBUILDING SERVICE

RETSCO, INC. can rebuild damaged or worn gauges to "like new" condition. Contact your RETSCO distributor or sales representatives for more information.